

DBV-2 SERIES, 2WATT, REGULATED WITH 2:1 INPUT RANGE

FEATURES:

- ✓ Wide (2:1) input voltage range
- ✓ 1500Vdc isolation voltage
- ✓ Regulated isolated twin output models
- ✓ Operating temperature range -40°C to +85°C
- ✓ Continuous short circuit protection
- ✓ 3 year warranty



Model	Input voltage (Vdc)	Output voltage (Vdc)	Output current (mA)		Efficiency Typ.
			Min.	Max.	
DBV2-0501	5(4.5~9)	5, 5	20	200	80%
DBV2-0502		9, 9	11	110	80%
DBV2-0503		12, 12	8.0	80	80%
DBV2-0504		15, 15	6.6	66	80%
DBV2-0505		24, 24	4.2	42	80%
DBV2-1201	12(9~18)	5, 5	20	200	80%
DBV2-1202		9, 9	11	110	80%
DBV2-1203		12, 12	8.0	80	80%
DBV2-1204		15, 15	6.6	66	80%
DBV2-1205		24, 24	4.2	42	80%
DBV2-2401	24(18~36)	5, 5	20	200	80%
DBV2-2402		9, 9	11	110	80%
DBV2-2403		12, 12	8.0	80	80%
DBV2-2404		15, 15	6.6	66	80%
DBV2-2405		24, 24	4.2	42	80%

Notes: other input and output models may available on request.

ELECTRICAL


Line regulation	---	±0.2%
Load regulation	10% ~ 100% full load	±0.5%
Ripple and noise	---	100mVp-p max.
Isolation voltage	---	1500Vdc
Short circuit protection	---	Continuous short circuit protection
Operating temperature range	---	-40°C to +85°C
MTBF	---	1000KHrs
Weight	---	4.5g

DBV-2 SERIES, 2WATT, REGULATED WITH 2:1 INPUT RANGE

ELECTRICAL

Notes: All the parameters are measured at 25°C ambient temperature, humidity < 75%, nominal input voltage, full load and after warm-up, unless otherwise specified.

MECHANICAL




CONNECTION

PIN #	ISOLATED TWIN
1	GND
2	+Vin
6	+Vo1
7	-Vo1
8	CS
9	-Vo2
10	+Vo2

Note:

* Unit is mm(inch).

ELECTRICAL CURVE



DBV-2 SERIES, 2WATT, REGULATED WITH 2:1 INPUT RANGE

NOTES

RECOMMENDED TEST AND APPLICATION CIRCUIT

ISOLATED TWIN OUTPUT

