

DHV-20 SERIES, 20WATT, 2:1 INPUT RANGE

FEATURES:

- ✓ Wide input range(2:1)
- ✓ Six-side shielded metal case
- ✓ Low ripple and noise
- ✓ Over current and short circuit protection
- ✓ Typical efficiency up to 90%
- ✓ 3 year warranty



Model	Input voltage (Vdc)	Output voltage (Vdc)	Output current (mA)	Efficiency Typ.
DHV20-1211*	12(9~18)	3.3	5000	86%
DHV20-1212*		5	4000	89%
DHV20-1216*		9	2222	85%
DHV20-1213		12	1667	89%
DHV20-1214*		15	1333	89%
DHV20-1215		24	834	90%
DHV20-2411	24(18~36)	3.3	5000	86%
DHV20-2412		5	4000	89%
DHV20-2416*		9	2222	85%
DHV20-2413*		12	1667	89%
DHV20-2414*		15	1333	89%
DHV20-2415*		24	834	90%
DHV20-4811*	48(36~72)	3.3	5000	86%
DHV20-4812*		5	4000	89%
DHV20-4816*		9	2222	85%
DHV20-4813*		12	1667	89%
DHV20-4814*		15	1333	89%
DHV20-4815*		24	834	90%

Notes:

1. Other input and output models may available on request;
2. Above models are default to metal case;
3. Add suffix "C" for CTRL pin function.

ELECTRICAL

Output voltage accuracy	+Vo	±2% max.
	-Vo	±3% max.
Line regulation	Nominal Load, full voltage	±0.5% max.
Load regulation	20% ~ 100% rated load	±1% max.
Ripple and noise	20MHz BM, full load	120mVp-p max.
Operating frequency	Typical value	300KHz typ.

DHV-20 SERIES, 20WATT, 2:1 INPUT RANGE

ELECTRICAL

Isolation voltage ($<1\text{mA}/\text{min}$)	Input to output	1500Vdc
Isolation resistance	---	1000m Ω
Temperature coefficient	---	$\pm 0.03\%/^{\circ}\text{C}$ max.
Operating temperature range	---	-40°C to $+85^{\circ}\text{C}$
Storage temperature range	---	-55°C to $+125^{\circ}\text{C}$
Short circuit protection	---	Continuous, auto-recovery
CTRL*	Turn on	Hang or connect high level(3.5-12Vdc)
	Turn off	Connect -Vin or low level(0-1.2Vdc)
	Shut off input current	1mA typ.
Cooling method	---	Cooling by air convection
Relative humidity	---	10%-90% max.
Weight	---	35g
MTBF	Bellcore TR-332, 25 $^{\circ}\text{C}$	1000KHrs

Notes: Unless otherwise specified, all the parameters of the test conditions are as follows: ambient temperature 25 $^{\circ}\text{C}$, the nominal input voltage, pure resistive nominal load.

*** The voltage of "CTRL" pin is almost equal to input "-Vin" pin**

DHV-20 SERIES, 20WATT, 2:1 INPUT RANGE

NOTES

RECOMMENDED TEST AND APPLICATION CIRCUIT

SINGLE OUTPUT

